

BLANK PAGE



ISO 6598: 1985

भारतीय मानक उर्वरकों के नमूने लेना और परीक्षण पद्धतियाँ भाग 3 फास्फोरस ज्ञात करना

अनुभाग 4 क्यूनोलीन फोसफोमोलीवडेट ग्रेवीमापी पद्धति

Indian Standard METHODS OF SAMPLING AND TEST FOR FERTILIZERS

PART 3 DETERMINATION OF PHOSPHORUS
Section 4 Quinoline Phosphomolybdate Gravimetric Method

ICS 65.080

© BIS 2004 **BUREAU OF INDIAN STANDARDS**MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

NATIONAL FOREWORD

This Indian Standard (Part 3/Sec 4) which is identical with ISO 6598: 1985 'Fertilizers — Determination of phosphorus content — Quinoline phosphomolybdate gravimetric method' issued by the International Organization for Standardization (ISO) was adopted by the Bureau of Indian Standards on the recommendations of the Fertilizers Sectional Committee and approval of the Petroleum, Coal and Related Products Division Council.

The text of ISO Standard has been proposed to be approved as suitable for publication as an Indian Standard without deviations. Certain conventions are, however, not identical to those used in Indian Standards. Attention is particularly drawn to the following:

- a) Wherever the words 'International Standard' appear referring to this standard, they should be read as 'Indian Standard'.
- b) Comma (,) has been used as a decimal marker while in Indian Standards, the current practice is to use a point (.) as the decimal marker.

CROSS REFERENCES

In this adopted standard reference appears to certain International Standards for which Indian Standards also exist. The corresponding Indian Standards, which are to be substituted in their places, are listed below along with their degree of equivalence for the editions indicated. However, that International Standard cross-referred in this adopted ISO Standard, which has subsequently been revised, position in respect of that latest ISO Standard has been given:

International Standard	Corresponding Indian Standard	Degree of Equivalence
ISO 5316 : 1977 Fertilizers — Extraction of water-soluble phosphates	IS 6092 (Part 3/Sec 3): 2004 Methods of sampling and test for fertilizers: Part 3 Determination of phosphorous, Section 3 Extraction of water-soluble phosphates	Identical
ISO 7497 : 1984 Fertilizers — Extraction of phosphates soluble in mineral acids	IS 6092 (Part 3/Sec 5): 2004 Methods of sampling and test for fertilizers: Part 3 Determination of phosphorus, Section 5 Extraction of phosphate soluble in mineral acids	do

ISO 6598: 1985

Indian Standard METHODS OF SAMPLING AND TEST FOR FERTILIZERS

PART 3 DETERMINATION OF PHOSPHORUS Section 4 Quinoline Phosphomolybdate Gravimetric Method

1 Scope and field of application

This International Standard specifies a gravimetric method using quinoline phosphomolybdate for the determination of phosphorus (expressed as diphosphorus pentaoxide) in a solution prepared from natural mineral phosphates or fertilizers.

2 References

ISO 5316, Fertilizers — Extraction of water-soluble phosphates.

ISO 7497, Fertilizers — Extraction of phosphates soluble in mineral acids.

3 Principle

Precipitation, after hydrolysis if necessary, of orthophosphate ions in the form of quinoline phosphomolybdate, in an acid medium and in the presence of acetone, at approximately 75 °C. Filtration, washing, drying and weighing of the precipitate obtained.

4 Reagents

During the analysis, use only reagents of recognized analytical grade and only distilled water or water of equivalent purity.

- 4.1 Acetone, pure.
- 4.2 Sodium molybdate dihydrate.
- 4.3 Quinoline, pure, distilled.
- 4.4 Citric acid monohydrate.
- **4.5** Nitric acid, $\varrho_{20} = 1{,}38 \text{ g/ml}$, 63 % (m/m) solution.

 ${\sf NOTE}-{\sf If}$ acid of another concentration is used, adjust the volume added accordingly.

- **4.6 Potassium dihydrogenorthophosphate**, previously dried at 105 °C.
- 4.7 Precipitation reagent, prepared as follows:

4.7.1 Solution A

Dissolve 70 g of the sodium molybdate dihydrate (4.2) in 100 ml of water in a 400 ml beaker.

4.7.2 Solution B

Dissolve 60 g of the citric acid monohydrate (4.4) in 100 ml of water in a 1 000 ml beaker. Add 85 ml of the nitric acid solution (4.5).

4.7.3 Solution C

Add solution A to solution B and mix.

4.7.4 Solution D

Mix 35 ml of the nitric acid solution (4.5) and 100 ml water in a 400 ml beaker and add 5 ml of the guinoline (4.3).

4.7.5 Solution E

Add solution D to solution C and mix. Leave overnight. Filter through a sintered glass filter, of porosity P 10 or P 16 (pore size index from 4 to 16 μ m) and, if necessary, filter the first part of the filtrate again until a clear filtrate is obtained.

Do not wash the residue with water. Add 280 ml of the pure acetone (4.1) to the filtrate and dilute to 1 000 ml with water.

The solution may be kept for 1 month in a stoppered bottle protected from sunlight and heat.

5 Apparatus

Usual laboratory equipment and in particular

- 5.1 Conical flask, wide necked, of capacity 500 ml.
- 5.2 Sintered glass filter crucible, of porosity P 10 or P 16 (pore size index from 4 to 16 μm).

ISO 6598: 1985

5.3 Oven, capable of being maintained at 250 \pm 5 °C.

5.4 Flameless heating apparatus.

5.5 Desiccator, containing silica gel.

6 Procedure

6.1 Aliquot portion

From the solution of fertilizer obtained by extraction in accordance with ISO 5316 or ISO 7497, take an aliquot portion containing preferably 10 to 20 mg of diphosphorus pentaoxide and not more than 20 ml of citrate solution.

Transfer to the conical flask (5.1). Add 25 ml of the nitric acid solution (4.5). Dilute to 100 ml with water.

6.2 Determination

6.2.1 Hydrolysis

If non-orthophosphates are present in the solution carry out a hydrolysis as follows.

Heat the contents of the conical flask gently until they begin to boil and boil until hydrolysis is complete (generally 1 h). Ensure that losses by splashing and excessive evaporation which would reduce the original volume by more than half are avoided, for example by using a reflux condenser system. When the hydrolysis is complete, make up to the original volume with water.

NOTE — If phosphorus is present in the form of orthophosphate only, the hydrolysis is not necessary.

6.2.2 Precipitation

Operating under a fume hood, add, without stirring, 100 ml of the precipitation reagent (4.7.5, solution E) from a measuring cylinder to the contents of the flask.

Cover with a watch-glass and heat the flask immediately using the apparatus (5.4) so that within 10 min boiling just starts (75 to 80 °C) and maintain for about 30 s. Then remove the flask from the heating apparatus and allow to cool for at least 30 min. Swirl 3 or 4 times during cooling. Allow to settle.

6.2.3 Weighing of the crucible

Heat the filter crucible (5.2) in the oven (5.3) maintained at 250 \pm 5 °C, to constant mass. Weigh the crucible to the nearest 0,000 1 g after cooling in a desiccator (5.5) containing silica gel in good condition.

6.2.4 Filtration and washing

Decant the supernatant liquid through the filter crucible (5.2), using suction. Wash the precipitate in the conical flask with 30 ml of water. Decant and filter the solution. Repeat this pro-

cedure five times. Quantitatively transfer the remainder of the precipitate into the crucible. Wash four times, adding the washing water only when filtration is practically complete. Continue to apply suction until all excess liquid has been extracted.

6.2.5 Drying and weighing

Wipe the outside of the crucible with a filter paper. Heat the crucible in the oven (5.3), maintained at 250 \pm 5 °C, to constant mass (15 to 30 min). Cool the crucible in a desiccator (5.5) containing silica gel in good condition, transfer to a balance and then weigh immediately to the nearest 0,000 1 g.

6.3 Check of reagents

For each series of determinations, carry out a check of the reagents using only the reagents and solvents in the proportions used for the extraction (citrate solution, etc.).

6.4 Check test

It is recommended that a determination on an aliquot portion, containing 10 mg of diphosphorus pentaoxide, of potassium dihydrogenorthophosphate (4.6) solution be carried out to check the validity of the method.

7 Expression of results

The diphosphorus pentaoxide content, expressed as a percentage by mass, is equal to

$$\frac{141,95}{4425,84} \times m_1 \times \frac{V_1}{V_0} \times \frac{100}{m_0} = 3,207 \times \frac{V_1}{V_0} \times \frac{m_1}{m_0}$$

where

 m_0 is the mass, in grams, of the test portion;

 m_1 is the mass, in grams, of the precipitate;

 V_0 is the volume, in millilitres, of the aliquot portion taken from the extraction solution;

 V_1 is the volume, in millilitres, of the extraction solution;

141,95 is the relative molecular mass of diphosphorus pentaoxide;

4 425,84 is twice the relative molecular mass of quinoline phosphomolybdate.

8 Precision

8.1 Repeatability

The absolute value of the difference between two individual results (mass of quinoline phosphomolybdate about 350 mg), using equal volumes of the same solution of extraction, under

ISO 6598:1985

the same conditions (same operator, same apparatus, same laboratory and short interval of time) shall be less than 2 mg.

8.2 Reproducibility

The absolute value of the difference between two individual results (mass of quinoline phosphomolybdate about 350 mg), using equal volumes of the same solutions of extraction, under different conditions (different operators, different apparatus, different laboratories and/or different times) shall be less than 6 mg.

9 Test report

The test report shall include the following information:

- a) the reference of the method used, i.e. ISO 6598;
- b) the results and the method of expression used;
- c) any unusual features noted during the determination;
- d) any operations not specified in this International Standard, or in the International Standards to which reference is made, or regarded as optional, together with any circumstances likely to have affected the results.

Bureau of Indian Standards

BIS is a statutory institution established under the *Bureau of Indian Standards Act*, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Review of Indian Standards

A ... - .. - I A I -

Amendments are issued to standards as the need arises on the basis of comments. Standards are also reviewed periodically; a standard along with amendments is reaffirmed when such review indicates that no changes are needed; if the review indicates that changes are needed, it is taken up for revision. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition by referring to the latest issue of 'BIS Catalogue' and 'Standards: Monthly Additions'.

This Indian Standard has been developed from Doc : No. PCD 20 (2184).

Amendments Issued Since Publication

Data of lance

Amend No.	Date of Issue	Text Affected	
	BUREAU OF INDIAN STANDARDS		
	BUILDO OF HADIAN STANDARDS		
Headquarters :			
Manak Bhavan, 9 Bahadur 3 Telephones : 2323 0131, 23	Shah Zafar Marg, New Delhi 110 002 23 33 75, 2323 9402	Telegrams : Manaksanstha (Common to all offices)	
Regional Offices:		Telephone	
Central : Manak Bhavan, NEW DELHI 11	9 Bahadur Shah Zafar Marg 0 002	{2323 7617 2323 3841	
Eastern : 1/14 C.I.T. Sche KOLKATA 700	eme VII M, V. I. P. Road, Kankurgachi 054	2337 8499, 2337 8561 2337 8626, 2337 9120	
Northern : SCO 335-336, \$	Sector 34-A, CHANDIGARH 160 022	∫60 3843 {60 9285	
Southern : C.I.T. Campus,	IV Cross Road, CHENNAI 600 113	{ 2254 1216, 2254 1442 2254 2519, 2254 2315	
Western : Manakalaya, E9 MUMBAI 400 09	9 MIDC, Marol, Andheri (East) 93	\$\int 2832 9295, 2832 7858 \\ 2832 7891, 2832 7892	
Branches : AHMEDABAD. B	ANGALORE. BHOPAL. BHUBANESHWA	R. COIMBATORE. FARIDABAD.	

GHAZIABAD. GUWAHATI? HYDERABAD. JAIPUR. KANPUR. LUCKNOW. NAGPUR. NALAGARH. PATNA. PUNE. RAJKOT. THIRUVANANTHAPURAM. VISAKHAPATNAM.

Tout Afforded